

IN THE CLAIMS:

1-12. (cancelled)

13. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling comprising;

a ~~sample container~~ a plurality of sample containers each for holding a PCR sample, ~~the each~~ sample container comprising an optically clear material, ~~the each~~ sample container formed for holding less than 1 milliliter of a sample and having a first side, a second side, and an end;

~~means for positioning the PCR sample container in a rotatable carousel to~~
move the sample containers one by one to a monitoring position;

means a forced air heater for simultaneously heating all the PCR samples in the carousel; ~~sample at a rate of at least 1.0°C/second;~~

means for simultaneously cooling all the PCR samples in the carousel; ~~sample at a rate of at least 1.0°C/second;~~

control means for repeatedly operating the ~~means for heating~~ forced air heater and the means for cooling to subject the PCR sample to thermal cycling;

means for optically exciting the sample in the monitoring position to cause the sample to fluoresce; and

means for detecting the fluorescence of the excited sample during amplification when the sample is in the monitoring position.

14. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 further comprising:

means for determining at least one reaction parameter in accordance with the detected fluorescence.

15. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 14 further comprising means for adjusting the control means in accordance with the reaction parameter.

16. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 15 in which the control means adjusts the operation of the ~~means for heating~~ forced air heater and the means for cooling to alter the times the means for heating and the means for cooling operate in accordance with the reaction parameter.

17. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 15 in which the control means adjusts the operation of the ~~means for heating~~ forced air heater and the means for cooling to alter the rate at which the biological sample is heated and cooled in accordance with the reaction parameter.

18. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the sample ~~container is~~ containers are fabricated at least partially from glass, the sample container having a volume not greater than about 10,000 μ l.

19. (cancelled)

20. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 further comprising means for positioning the means for optically exciting the sample and the means for detecting the fluorescence of excited sample to optimize the fluorescence which is detected.

21. (cancelled)

22. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the means for cooling comprises an air movement mechanism which transports ambient air to the sample ~~container~~ containers.

23. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the control means comprises a microprocessor.

24. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the means for optically exciting the sample comprises a photo emitter structure positioned so that the radiation emitted therefrom impinges the first side of the sample container in the monitoring position.

25. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 24 wherein means for detecting the fluorescence of the excited sample comprises a photo detector structure positioned so that the radiation emitted from the second side of the sample container in the monitoring position is detected.

26. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the means for optically

exciting the sample comprises a photo emitter structure positioned so that the radiation emitted therefrom impinges the end of the sample container in the monitoring position.

27. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 26 wherein the means for detecting the fluorescence of the excited sample comprises a photo detector structure positioned so that the radiation emitted from the end of the sample container in the monitoring position is detected.

28. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 14 wherein the means for determining at least one reaction parameter in accordance with the detected fluorescence comprises means for determining at least one reaction parameter selected from the group consisting of: product melting temperature, product melting time, product reannealing temperature, product reannealing time, probe melting time, primer annealing/extension temperature, and primer annealing/extension time.

29. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the control means comprises means cooling the sample when the means for detecting the fluorescence of the excited sample detects that the product is completely melted.

30. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the control means comprises means for heating the sample when the means for detecting the fluorescence of the excited sample detects no more product generation.

31. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the means for optically exciting is positioned to interact with the first side of the sample container in the monitoring position and the means for detecting the fluorescence is positioned to interact with the second side of the sample container in the monitoring position.

32. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 13 wherein the means for optically exciting is positioned to interact with the end of the sample container and the means for detecting the fluorescence is positioned to interact with the end of the sample container.

33. (currently amended) A system for performing PCR and monitoring the reaction in real time during temperature cycling comprising:

a plurality of sample containers for holding a plurality of PCR samples, each sample container comprising an optically clear capillary tube, each sample container formed for holding less than 1 milliliter of a sample and having a sealed end and an open end with a sealable closure on the open end;

~~means for holding a plurality of sample containers, the means for holding comprising a rotatable carousel formed for holding the sample containers~~ to move the sample containers one by one to a monitoring position;

means for forcing hot gas into contact with the plurality of sample containers in the carousel;

means for forcing cool gas into contact with the plurality of sample containers in the carousel;

means for repeatedly operating the means for forcing hot gas and the means for forcing cool gas to subject the PCR samples to thermal cycling;

means for optically exciting at least one selected PCR sample to cause the selected PCR sample to fluoresce;

means for detecting the fluorescence of the excited selected PCR sample at both a first wavelength and a second wavelength; and

means for determining at least one reaction parameter for the selected PCR sample in accordance with the fluorescence at the first and second wavelengths and displaying the reaction parameter in a visually perceptible manner in real time.

34. (original) A system for performing PCR and monitoring the reaction in real time during temperature cycling as defined in claim 33 further comprising means for adjusting the means for repeatedly operating in accordance with the reaction parameter such that the reaction is adjusted in real time.

35. (original) A system for performing PCR and monitoring the reaction in real time during temperature cycling as defined in claim 33 wherein the means for determining at least one reaction parameter in accordance with the detected fluorescence at the first and second wavelengths and displaying the reaction parameter in a visually perceptible manner in real time comprises means for determining a reaction parameter selected from the group consisting of denaturation temperature and time, primer annealing temperature and time, probe annealing temperature and time, enzyme extension temperature and time, and number of cycles.

36-54. (cancelled)

55. (currently amended) A system for carrying out and monitoring the progress of first and second biological reactions comprising:

first holding means for holding a first biological sample;

second holding means for holding a second biological sample;

transporting means for moving the first and second holding means between a non monitoring position and a monitoring position;

thermal cycling means for repeatedly heating and cooling the first holding means and the second holding means in both the non monitoring position and in the monitoring position to carry out thermal cycling simultaneously on both the first biological sample and the second biological sample, the thermal cycling means comprising a forced air heater and a fan ~~means for heating selected from the group consisting of hot gas, a lamp, and infrared radiation and a means for cooling comprising cool air flow;~~

monitoring means for ascertaining the progress of the first biological reaction in the first means for holding and the second biological reaction in the second means for holding when the first and second biological samples are in the monitoring position, the means for monitoring comprising means for detecting radiation emitted from the first and second biological samples; and

controlling means for controlling the operation of the transporting means, thermal cycling means, and the monitoring means such that the progress of the first and second biological reactions is detected as thermal cycling occurs.

56. (previously presented) A system for carrying out and monitoring the progress of first and second biological reactions as defined in claim 55 wherein the monitoring means comprises:

an excitation source emitting excitation radiation;

means for directing the excitation radiation to the monitoring position such that when the first and second biological samples are located at the monitoring position the samples emit radiation;

means for converting the emitted radiation to an electrical signal;

means for processing the electrical signal to arrive at a reaction parameter;

means for displaying the reaction parameter; and

means for recording the reaction parameter.

57. (previously presented) A system for carrying out and monitoring the progress of first and second biological reactions as defined in claim 56 wherein the reaction parameter is selected from the group consisting of denaturation temperature and time, primer

annealing temperature and time, probe annealing temperature and time, enzyme extension temperature and time, and number of cycles.

58. (previously presented) A system for carrying out and monitoring the progress of first and second biological reactions as defined in claim 56 wherein:

the excitation source comprises a photo-emitting source, the photo-emitting source selected from the group consisting of a xenon lamp and a light emitting diode;

the means for converting the emitted radiation to an electrical signal comprises a photo-detection device, the photo-detection device selected from the group consisting of a photo-multiplier tube and a photo-diode; and

the means for processing the electrical signal to arrive at a reaction parameter comprises a microprocessor.

59. (previously presented) A system for carrying out and monitoring the progress of first and second biological reactions as defined in claim 58 wherein the means for converting the emitted radiation to an electrical signal comprises a first photo-detection device, the first photo-detection device is selected from the group consisting of a photo-multiplier tube and a photo-diode and a second photo-detection device selected from the group consisting of a photo-multiplier tube and a photo-diode.

60-78. (cancelled)

79. (currently amended) A device for monitoring the fluorescence of a sample plurality of samples each held within a its respective sample vessel, said device comprising

a chamber;

~~a sample vessel holder for holding the sample vessel, said sample vessel holder located within said chamber;~~ a carousel for holding a plurality of sample vessels and moving each sample vessel sequentially to a monitoring position, said carousel being rotatably mounted in said chamber, and said each sample vessel comprising an optically transparent material and walls defining a volume having at least first and second dimensions wherein the first dimension is less than the second dimension and wherein the ratio of volume to external surface area of the vessel is less than 1mm;

a stepper motor for rotating said carousel;

means for coupling said carousel to said motor;

a heater and a fan in air flow communication with the chamber and a controller therefor for rapidly cycling the temperature of the chamber;

a light emitting source mounted in said chamber and positioned to illuminate the sample vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel; and

a light detector mounted in said chamber and positioned to measure fluorescence from the sample vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel.

80. (currently amended) The device of claim 79 ~~wherein the sample vessel holder comprises a carousel for holding a plurality of sample vessels, said carousel being rotatably mounted in said chamber, said device further comprising~~

~~a stepper motor for rotating said carousel; and
means for coupling said carousel to said motor;~~
wherein said sample vessels are capillary tubes.

81. (cancelled)

82. (currently amended) A device for conducting PCR reactions, said device comprising a chamber;

a heater and a fan mounted in said device and in air flow communication with the chamber;

a carousel for holding a plurality of sample vessels, said carousel being rotatably mounted in said chamber to move the sample vessels one by one to a monitoring position, said heater and fan positioned to heat and cool simultaneously the plurality of sample vessels held in the carousel;

each of said sample vessels comprising an optically transparent material and walls defining a volume having at least first and second dimensions wherein the first dimension is less than the second dimension and wherein the ratio of volume to external surface area of each of said sample vessels is less than 1mm;

a light emitting source mounted in said chamber and positioned to illuminate at least one selected sample vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the selected sample vessel; and

a light detector mounted in said chamber and positioned to measure fluorescence from the selected sample vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the selected sample vessel.

83-86. (cancelled)

87. (currently amended) A system for performing PCR and monitoring the reaction comprising;

a chamber;

a heater and a fan in air flow communication with the chamber and a controller for cycling the temperature in the chamber according to initial predefined temperature and time parameters;

a carousel for holding a plurality of sample vessels said carousel being rotatably mounted in said chamber to move the sample vessels sequentially to a monitoring position, the carousel positioned such that the heater and the fan simultaneously heat and cool each of the samples in the carousel, said sample vessels comprising an optically transparent material and walls defining a volume having at least first and second dimensions wherein the first dimension is less than the second dimension and wherein the ratio of volume to external surface area of the vessel is less than 1mm;

a light emitting source mounted in said chamber and positioned to illuminate at least one of the sample vessels in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel;

a light detector mounted in said chamber and positioned to measure fluorescence from at least one of the sample vessels in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel; and

means for displaying the status of the reaction based on detected fluorescence.

88. (original) The system of claim 87 further comprising means for adjusting the controller such that one or more reaction parameters the reaction is adjusted in real time.

89. (original) The system of claim 87 or 88 wherein the carousel comprises:

a disc having a top surface, a bottom surface, an outer edge extending therebetween, a sample receiving port in the top surface, a sample vessel port in the outer edge, and a sample passageway communicating with said sample receiving port and the sample vessel port, said sample vessel port and passageway formed for receiving and fixing a sample vessel to the disc.

90. (previously presented) The system of claim 87 or 88 wherein the sample vessels are capillary tubes each having an inner diameter ranging from about 0.02mm to about 1.0mm.

91. (original) The system of claim 89 wherein the passageway of the carousel includes a barrier that prevents a liquid sample delivered through the sample

receiving port from flowing to the sample vessel port absent a biasing force on said liquid sample.

92. (original) The system of claim 89 further comprising a motor for rotating the carousel to provide a biasing force on a liquid sample delivered through the sample receiving port.

93-120. (cancelled)

121. (currently amended) A device for conducting PCR reactions, said device comprising

a chamber;

a heater and a fan mounted in said device and in air flow communication with the chamber;

a carousel for holding a plurality of sample vessels, said carousel being rotatably mounted in said chamber to move the sample vessels sequentially to a monitoring position, the carousel positioned such that the heater and the fan simultaneously heat and cool each of the samples in the carousel;

said sample vessels comprising an optically transparent material and walls defining a volume having at least first and second dimensions wherein the first dimension is less than the second dimension and wherein the ratio of volume to external surface area of each of said sample vessels is less than 1mm;

a light emitting source positioned to illuminate ~~at least one~~ the selected sample vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the selected sample vessel; and

a light detector positioned to measure fluorescence from the selected sample vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the selected sample vessel.

122. (currently amended) A system for performing PCR and monitoring the reaction comprising:

a chamber;

a heater and a fan in air flow communication with the chamber and a controller for cycling the temperature in the chamber according to initial predefined temperature and time parameters;

a carousel for holding a plurality of sample vessels said carousel being rotatably mounted in said chamber to move the sample vessels sequentially to a monitoring position, the carousel positioned such that the heater and the fan simultaneously heat and cool

each of the samples in the carousel, said sample vessels comprising an optically transparent material and walls defining a volume having at least first and second dimensions wherein the first dimension is less than the second dimension and wherein the ratio of volume to external surface area of the vessel is less than 1mm;

a light emitting source positioned to illuminate ~~at least one of the sample vessels~~ vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel;

a light detector positioned to measure fluorescence from ~~at least one of the sample vessels~~ the sample vessel in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel; and

means for displaying the status of the reaction based detected fluorescence.

123. (previously presented) The system of claim 122 further comprising means for adjusting the controller such that one or more reaction parameters the reaction is adjusted during temperature cycling.

124. (previously presented) The system of claim 122 wherein the carousel comprises:

a disc having a top surface, a bottom surface, an outer edge extending therebetween, a sample receiving port in the top surface, a sample vessel port in the outer edge, and a sample passageway communicating with said sample receiving port and the sample vessel port, said sample vessel port and passageway formed for receiving and fixing a sample vessel to the disc.

125. (previously presented) The system of claim 122 wherein the sample vessels are capillary tubes each having an inner diameter ranging from about 0.02 mm to about 1.0 mm.

126. (previously presented) The system of claim 124 wherein the passageway of the carousel includes a barrier that prevents a liquid sample delivered through the sample receiving port from flowing to the sample vessel port absent a biasing force on said liquid sample.

127. (previously presented) The system of claim 124 further comprising a motor for rotating the carousel to provide a biasing force on a liquid sample delivered through the sample receiving port.

128. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling comprising;

a ~~sample container~~ plurality of sample containers each for holding a PCR sample, ~~the each~~ sample container comprising an optically clear material, ~~the each~~ sample container formed for holding less than 1 milliliter of a sample and having a first side, a second side, and an end;

means for ~~positioning the PCR sample container in~~ moving the sample containers sequentially into and out of a monitoring position;

~~means a forced air heater~~ for heating ~~the each~~ PCR sample simultaneously in or out of the monitoring position at a rate of at least 0.5°C/second;

means for cooling ~~the each~~ PCR sample simultaneously in or out of the monitoring position at a rate of at least 0.5°C/second;

control means for repeatedly operating the ~~means for heating forced air heater~~ and the means for cooling to subject the PCR sample to thermal cycling;

means for optically exciting the sample in the monitoring position to cause the sample to fluoresce;

means for detecting the fluorescence of the excited sample during amplification when the sample container is in the monitoring position;

means for determining at least one reaction parameter in accordance with the detected fluorescence; and

means for adjusting the control means in accordance with the reaction parameter.

129. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 in which the control means adjusts the operation of the means for heating and the means for cooling to alter the times the ~~means for heating forced air heater~~ and the means for cooling operate in accordance with the reaction parameter.

130. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 in which the control means adjusts the operation of the ~~means for heating forced air heater~~ and the means for cooling to alter the rate at which the biological sample is heated and cooled in accordance with the reaction parameter.

131. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the means for ~~positioning moving the PCR sample container in a monitoring position~~ containers comprises a rotatable carousel.

132. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 further comprising means for positioning the means for optically exciting the sample and the means for detecting the fluorescence of excited sample to optimize the fluorescence which is detected.

133. cancelled.

134. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the means for cooling comprises an air movement mechanism which transports ambient air to the sample container.

135. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the control means comprises a microprocessor.

136. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the means for optically exciting the sample comprises a photo emitter structure positioned so that the radiation emitted therefrom impinges the first side of the sample container in the monitoring position.

137. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 136 wherein means for detecting the fluorescence of the excited sample comprises a photo detector structure positioned so that the radiation emitted from the second side of the sample container in the monitoring position is detected.

138. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the means for optically exciting the sample comprises a photo emitter structure positioned so that the radiation emitted therefrom impinges the end of the sample container in the monitoring position.

139. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 138 wherein the means for detecting the fluorescence of the excited sample comprises a photo detector structure positioned so that the radiation emitted from the end of the sample container in the monitoring position is detected.

140. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the means for determining at least one reaction parameter in accordance with the detected fluorescence comprises means for determining at least one reaction parameter selected from the group

consisting of: product melting temperature, product melting time, product reannealing temperature, product reannealing time, probe melting time, primer annealing/extension temperature, and primer annealing/extension time.

141. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the control means comprises means cooling the sample when the means for detecting the fluorescence of the excited sample detects that the product is completely melted.

142. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the control means comprises means for heating the sample when the means for detecting the fluorescence of the excited sample detects no more product generation.

143. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the means for optically exciting is positioned to interact with the first side of the sample container in the monitoring position and the means for detecting the fluorescence is positioned to interact with the second side of the sample container in the monitoring position.

144. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 128 wherein the means for optically exciting is positioned to interact with the end of the sample container in the monitoring position and the means for detecting the fluorescence is also positioned to interact with the end of the sample container in the monitoring position.

145. (currently amended) A system for performing PCR and monitoring the reaction in real time during temperature cycling comprising:

a plurality of sample containers for holding a plurality of PCR samples, each sample container comprising an optically clear capillary tube, each sample container formed for holding less than 1 milliliter of a sample and having a sealed end and an open end with a sealable closure on the open end;

~~means for holding a plurality of sample containers, the means for holding comprising a rotatable carousel formed for holding the sample containers~~ to move the sample containers one by one to a monitoring position;

means for forcing hot gas into contact with the plurality of sample containers in the carousel;

means for forcing cool gas into contact with the plurality of sample containers in the carousel;

means for repeatedly operating the means for forcing hot gas and the means for forcing gas fluid to subject the PCR samples to thermal cycling;

means for optically exciting at least one selected PCR sample to cause the selected PCR sample to fluoresce;

means for detecting the fluorescence of the excited selected PCR sample at both a first wavelength and a second wavelength;

means for determining at least one reaction parameter for the selected PCR sample in accordance with the detected fluorescence at the first and second wavelengths and displaying the reaction parameter in a visually perceptible manner in real time; and

means for adjusting the means for repeatedly operating in accordance with the reaction parameter such that the reaction is adjusted in real time.

146. (previously presented) A system for performing PCR and monitoring the reaction in real time during temperature cycling as defined in claim 145 wherein the means for determining at least one reaction parameter in accordance with the detected fluorescence at the first and second wavelengths and displaying the reaction parameter in a visually perceptible manner in real time comprises means for determining a reaction parameter selected from the group consisting of denaturation temperature and time, primer annealing temperature and time, probe annealing temperature and time, enzyme extension temperature and time, and number of cycles.

147. (currently amended) A system for performing PCR and monitoring the reaction in real time comprising;

a chamber;

a heater and a fan mounted in air flow communication with the chamber and a controller for cycling the temperature in the chamber according to initial predefined temperature and time parameters;

a carousel for holding a plurality of sample vessels said carousel being rotatably mounted in said chamber to move the sample vessels sequentially to a monitoring position, said sample vessels comprising an optically transparent material and walls defining a volume having at least first and second dimensions wherein the first dimension is less than the second dimension and wherein the ratio of volume to external surface area of the vessel is less than 1mm;

a light emitting source mounted in said chamber and positioned to illuminate at least one of the sample vessels in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel;

a light detector mounted in said chamber and positioned to measure fluorescence from at least one of the sample vessels in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel;

means for displaying the status of the reaction based detected fluorescence;

and

means for adjusting the controller such that one or more reaction parameters the reaction is adjusted in real time.

148. (previously presented) The system of claim 147 wherein the carousel comprises:

a disc having a top surface, a bottom surface, an outer edge extending therebetween, a sample receiving port in the top surface, a sample vessel port in the outer edge, and a sample passageway communicating with said sample receiving port and the sample vessel port, said sample vessel port and passageway formed for receiving and fixing a sample vessel to the disc.

149. (previously presented) The system of claim 148 wherein the passageway of the carousel includes a barrier that prevents a liquid sample delivered through the sample receiving port from flowing to the sample vessel port absent a biasing force on said liquid sample.

150. (previously presented) The system of claim 149 further comprising a motor for rotating the carousel to provide the biasing force on the liquid sample to deliver the liquid sample through the sample receiving port.

151. (previously presented) The system of claim 147 wherein the sample vessels are capillary tubes having an inner diameter ranging from about 0.02mm to about 1.0mm.

152. (previously presented) A system for performing PCR and monitoring the reaction comprising:

a chamber;

a heater and a fan in air flow communication with the chamber and a controller for cycling the temperature in the chamber according to initial predefined temperature and time parameters;

a carousel for holding a plurality of sample vessels said carousel being rotatably mounted in said chamber to move the sample vessels one by one to a monitoring position; the carousel comprising a disc having a top surface, a bottom surface, and an outer edge extending therebetween, a sample receiving port in the top surface, a sample vessel port

in the outer edge, and a sample passageway communicating with said sample receiving port and the sample vessel port, said sample vessel port and passageway formed for receiving and fixing a sample vessel to the disc; the passageway including a barrier that prevents a liquid sample delivered through the sample receiving port from flowing to the sample vessel port absent a biasing force on said liquid sample;

said sample vessels comprising an optically transparent material and walls defining a volume having at least first and second dimensions wherein the first dimension is less than the second dimension and wherein the ratio of volume to external surface area of the vessel is less than 1mm;

a light emitting source positioned to illuminate at least one of the sample vessels in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel;

a light detector positioned to measure fluorescence from at least one of the sample vessels in the monitoring position along an axis substantially parallel to a wall along the second dimension of the vessel; and

a display for displaying the status of the reaction based detected fluorescence.

153. (previously presented) The system of claim 152 further comprising a motor for rotating the carousel to provide a biasing force on a liquid sample delivered through the sample receiving port.

154. (previously presented) The system of claim 152 further comprising an adjuster for adjusting the controller such that one or more reaction parameters the reaction is adjusted in real time.

155. (previously presented) The system of claim 152 wherein the sample vessels are capillary tubes each having an inner diameter ranging from about 0.02 mm to about 1.0 mm.

156. (currently amended) The system of claim 13 ~~wherein the means for positioning comprises~~ further comprising a movable platform on which the means for optically exciting and means for detecting are mounted.

157. (previously presented) The system of claim 13 wherein the means for detecting the fluorescence of the excited sample during amplification detects fluorescence throughout temperature cycling.

158. (previously presented) The system of claim 13 wherein the means for detecting the fluorescence of the excited sample during amplification detects fluorescence during an extension or combined annealing/extension phase of temperature cycling.

160. (previously presented) The system of claim 13 wherein the rate of heating the PCR sample and the rate of cooling the PCR sample is at least 4.0°C/second.

161-168. (Cancelled)

169. (currently amended) The system for carrying out and monitoring the progress of first and second biological reactions as defined in claim ~~168~~ 55 wherein the thermal cycling means heats and cools the first holding means and the second holding means at a rate of at least 1.0°C/second.

170. (previously presented) The system for carrying out and monitoring the progress of first and second biological reactions as defined in claim ~~168~~ 55 wherein the thermal cycling means heats and cools the first holding means and the second holding means at a rate of at least 4.0°C/second

171. (currently amended) The system for carrying out and monitoring the progress of first and second biological reactions as defined in claim ~~168~~ 55 wherein the thermal cycling means heats and cools the first holding means and the second holding means at a rate of at least 10°C/second.

172. (currently amended) The system for carrying out and monitoring the progress of first and second biological reactions as defined in claim ~~168~~ 55 wherein the thermal cycling means heats and cools the first holding means and the second holding means at a rate of at least 200°C/second.

173. (currently amended) A system for performing PCR and monitoring the reaction during temperature cycling comprising;

a sample container for holding a PCR sample, the sample container comprising an optically clear material, the sample container formed for holding less than 1 milliliter of a sample and having a first side, a second side, and an end;

means for positioning the PCR sample container in a monitoring position;

means for heating the PCR sample at a rate of at least 10°C/second;

means for cooling the PCR sample at a rate of at least 10°C/second;

control means for repeatedly operating the means for heating and the means for cooling to subject the PCR sample to thermal cycling;

means for optically exciting the sample to cause the sample to fluoresce; and

means for detecting the fluorescence of the excited sample during amplification when the sample is in the monitoring position.

174. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 further comprising:

means for determining at least one reaction parameter in accordance with the detected fluorescence.

175. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 174 further comprising means for adjusting the control means in accordance with the reaction parameter.

176. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 175 in which the control means adjusts the operation of the means for heating and the means for cooling to alter the times the means for heating and the means for cooling operate in accordance with the reaction parameter.

177. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 175 in which the control means adjusts the operation of the means for heating and the means for cooling to alter the rate at which the biological sample is heated and cooled in accordance with the reaction parameter.

178. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the sample container is fabricated at least partially from glass, the sample container having a volume not greater than about 10,000 μ l.

179. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the means for positioning the PCR sample container in a monitoring position comprises a rotatable carousel.

180. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 further comprising means for positioning the means for optically exciting the sample and the means for detecting the fluorescence of excited sample to optimize the fluorescence which is detected.

181. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the means for heating the PCR sample comprises a forced air heater.

182. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the means for cooling comprises an air movement mechanism which transports ambient air to the sample container.

183. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the control means comprises a microprocessor.

184. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the means for optically exciting the sample comprises a photo emitter structure positioned so that the radiation emitted therefrom impinges the first side of the sample container.

185. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 184 wherein means for detecting the fluorescence of the excited sample comprises a photo detector structure positioned so that the radiation emitted from the second side of the sample container is detected.

186. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the means for optically exciting the sample comprises a photo emitter structure positioned so that the radiation emitted therefrom impinges the end of the sample container.

187. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 186 wherein the means for detecting the fluorescence of the excited sample comprises a photo detector structure positioned so that the radiation emitted from the end of the sample container is detected.

188. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 174 wherein the means for determining at least one reaction parameter in accordance with the detected fluorescence comprises means for determining at least one reaction parameter selected from the group consisting of: product melting temperature, product melting time, product reannealing temperature, product reannealing time, probe melting time, primer annealing/extension temperature, and primer annealing/extension time.

189. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the control means comprises means cooling the sample when the means for detecting the fluorescence of the excited sample detects that the product is completely melted.

190. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the control means comprises means for heating the sample when the means for detecting the fluorescence of the excited sample detects no more product generation.

191. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the means for optically exciting is positioned to interact with the first side of the sample container and the means for detecting the fluorescence is positioned to interact with the second side of the sample container.

192. (previously presented) A system for performing PCR and monitoring the reaction during temperature cycling as defined in claim 173 wherein the means for optically exciting is positioned to interact with the end of the sample container and the means for detecting the fluorescence is positioned to interact with the end of the sample container.

193. (previously presented) The system of claim 173 wherein the rate of heating the PCR sample and the rate of cooling the PCR sample is at least 20°C/second.

194. (previously presented) A system for carrying out and monitoring the progress of first and second biological reactions comprising:

first holding means for holding a first biological sample;

second holding means for holding a second biological sample;

transporting means for moving the first and second holding means between a non-monitoring position and a monitoring position;

thermal cycling means for repeatedly heating and cooling the first holding means and the second holding means in both the non-monitoring position and in the monitoring position to carry out thermal cycling on both the first biological sample and the second biological sample, wherein the thermal cycling means heats and cools the first holding means and the second holding means at a rate of at least 10°C/second;

monitoring means for ascertaining the progress of the first biological reaction in the first means for holding and the second biological reaction in the second means for holding when the first and second biological samples are in the monitoring position, the means for monitoring comprising means for detecting radiation emitted from the first and second biological samples; and

controlling means for controlling the operation of the transporting means, thermal cycling means, and the monitoring means such that the progress of the first and second biological reactions is detected as thermal cycling occurs.

195. (previously presented) The system of claim 194 wherein the thermal cycling means heats and cools the first holding means and the second holding means at a rate of at least 20°C/second.

196. (cancelled)

197. (new) The system of claim 13 wherein the rate of heating the PCR sample and the rate of cooling the PCR sample is at least 1.0°C/second.